

Stefano Tornincasa

Technical Drawing for Product Design

Mastering ISO GPS and ASME GD&T

 Springer

Contents

| | | |
|----------|---|----|
| 1 | Introducing GD&T and GPS | 1 |
| 1.1 | The Shortcoming of Traditional Coordinate Tolerancing | 1 |
| 1.2 | Traditional Dimensioning Example | 4 |
| | Reference | 9 |
| 2 | The Geometrical Product Specification (GPS) Language | 11 |
| 2.1 | General Concepts | 11 |
| 2.2 | Classification of Geometric Tolerances | 17 |
| 2.3 | The Specification World: Types and Symbols of Geometrical Tolerances | 20 |
| 2.3.1 | ISO Tolerance Indicator | 20 |
| 2.3.2 | Drawing Geometrical Specifications | 22 |
| 2.3.3 | Additional Symbols of the ISO 1101 and ISO 5458 Standards | 25 |
| 2.3.4 | New Symbols and Specification Modifiers of ISO 5458:2018 | 38 |
| 3 | Dimensioning with Geometrical Tolerances | 41 |
| 3.1 | Conversion from Traditional 2D Coordinate Tolerancing | 41 |
| 3.2 | Advantages of Geometrical Product Specification | 44 |
| 4 | The GPS and GD&T Language | 49 |
| 4.1 | Historical Evolution of the ISO and ASME Standards | 49 |
| 4.1.1 | The Birth of Tolerances | 50 |
| 4.2 | The GPS Matrix Model | 52 |
| 4.3 | The Fundamental ISO 8015 Standard | 54 |
| 4.3.1 | The Effect of ISO 8015 on Technical Documentation | 56 |
| 4.3.2 | The Main Concepts Defined in ISO 8015:2011 | 59 |
| 4.4 | General Geometric Tolerances | 60 |
| 4.4.1 | The New ISO 22081 Standard | 62 |

| | | |
|----------|--|------------|
| 4.5 | The New ASME Y14.5:2018 Standard | 65 |
| 4.5.1 | The Envelope Requirement or Rule#1 of the ASME Standard | 67 |
| 4.6 | The Main Differences Between ISO GPS and ASME GD&T Standards | 72 |
| 4.6.1 | The Different Concepts of Pattern and Simultaneous Requirement. | 77 |
| | References | 79 |
| 5 | Interdependence Between Dimensions and Geometry | 81 |
| 5.1 | MMR and LMR Requirements | 81 |
| 5.1.1 | Maximum Material Requirement (MMR). | 82 |
| 5.1.2 | Least Material Requirement (LMR). | 86 |
| 5.1.3 | Reciprocity Requirement (RPR) | 89 |
| 5.2 | Direct Indication of Virtual Size | 92 |
| 5.3 | When to Use MMR, LMR, and RFS | 94 |
| 5.4 | The MMR and LMR Requirements in the ASME Standards | 97 |
| 6 | Datums and Datum Systems | 105 |
| 6.1 | Datum Systems | 105 |
| 6.1.1 | Association of Datums | 108 |
| 6.1.2 | Datum: Mathematical Concepts | 110 |
| 6.2 | Indication of Datum Features in Technical Documentation | 112 |
| 6.3 | The Datum Systems in ASME Y14.5 | 114 |
| 6.3.1 | Establishing a Datum | 117 |
| 6.3.2 | Location of a Workpiece in a Datum Reference Frame | 119 |
| 6.3.3 | Selection of Datum Features | 123 |
| 6.4 | Examples of Datum Systems in the ISO Standards | 127 |
| 6.4.1 | Datum System with Three Single Datums | 128 |
| 6.5 | Type of Datum | 130 |
| 6.5.1 | Centerplanes (Width-Type Features of Size). | 130 |
| 6.5.2 | Common Datum. | 133 |
| 6.5.3 | Conical Surfaces as Datum Features | 139 |
| 6.6 | Datum Features Referenced at MMR and LMR (Size Datum) | 140 |
| 6.7 | Locked or Released Degrees of Freedom from a Datum | 145 |
| 6.7.1 | Customised Datum Reference Frame in the ASME Standards | 147 |
| 6.8 | Datum Targets | 149 |
| 6.8.1 | Contacting Feature | 155 |
| 6.8.2 | Datum Targets in the ASME Standards | 159 |
| | References | 161 |

| | | |
|----------|---|-----|
| 7 | Form Tolerances | 163 |
| 7.1 | Introduction | 163 |
| 7.2 | Straightness Tolerance | 163 |
| 7.2.1 | Straightness Parameters | 166 |
| 7.2.2 | Straightness Tolerance Applied to a Feature of Size | 168 |
| 7.2.3 | Straightness Tolerance in the ASME Standards | 171 |
| 7.3 | Flatness Tolerance | 172 |
| 7.3.1 | Flatness Parameters | 174 |
| 7.3.2 | Flatness Control | 176 |
| 7.3.3 | Flatness Tolerance in the ASME Standards | 177 |
| 7.4 | Roundness | 178 |
| 7.4.1 | Roundness Parameters | 180 |
| 7.4.2 | Roundness Tolerance in the ASME Standards | 183 |
| 7.5 | Cylindricity | 185 |
| 7.5.1 | Cylindricity Parameters | 187 |
| 7.5.2 | Cylindricity Tolerance in the ASME Standards | 189 |
| | Reference | 190 |
| 8 | Orientation Tolerances | 191 |
| 8.1 | Introduction | 191 |
| 8.2 | Parallelism | 192 |
| 8.2.1 | Parallelism of a Median Line Related to a Datum System | 192 |
| 8.2.2 | Parallelism of a Set of Lines on a Surface Related to a Datum Plane | 194 |
| 8.2.3 | Parallelism of a Planar Surface Related to a Datum System | 195 |
| 8.3 | Perpendicularity | 195 |
| 8.3.1 | Perpendicularity of a Median Line Related to a Datum System | 196 |
| 8.3.2 | Perpendicularity of a Median Line Related to a Datum Straight Line | 197 |
| 8.3.3 | Perpendicularity of a Median Line Related to a Datum Plane | 197 |
| 8.3.4 | Perpendicularity of a Planar Surface Related to a Datum Plane | 198 |
| 8.3.5 | Perpendicularity (MMR) Applied to a Feature of Size | 200 |
| 8.4 | Angularity | 201 |
| 8.4.1 | Angularity of a Median Line Related to a Datum Straight Line | 201 |
| 8.4.2 | Angularity of a Median Line Related to a Datum System | 201 |

| | | |
|-----------|--|------------|
| 8.4.3 | Angularity of a Planar Surface Related to a Datum Plane | 202 |
| 8.4.4 | Angularity (MMR) Applied to a Feature of Size | 204 |
| 8.5 | Orientation Tolerances in the ASME Standards | 204 |
| | Reference | 206 |
| 9 | Location Tolerances | 207 |
| 9.1 | Introduction | 207 |
| 9.2 | Position Tolerances | 209 |
| 9.2.1 | Position Tolerance Applied to Median Surfaces | 212 |
| 9.2.2 | Choice of the Modifiers for Position Tolerances | 214 |
| 9.2.3 | Pattern Location | 221 |
| 9.2.4 | Calculation of a Geometrical Position Tolerance | 226 |
| 9.2.5 | Projected Tolerance Zone | 231 |
| 9.2.6 | Position Tolerances in the ASME Standards | 235 |
| 9.3 | Concentricity and Coaxiality Tolerances | 242 |
| 9.3.1 | Concentricity in ASME Y14.5 | 244 |
| 9.4 | Symmetry Tolerances | 245 |
| 9.4.1 | Symmetry in ASME Y14.5 | 246 |
| 10 | Profile Tolerances | 249 |
| 10.1 | Introduction | 249 |
| 10.2 | Rules for Profile Tolerancing (ISO 1660:2017) | 252 |
| 10.3 | Profile Interpretation | 255 |
| 10.4 | Offset Tolerance Zone Specification | 257 |
| 10.5 | Constraint Specification Elements | 258 |
| 10.5.1 | Offset Tolerance Zone with an Unspecified Linear Offset | 258 |
| 10.5.2 | Offset Tolerance Zone with an Unspecified Angular Offset | 260 |
| 10.6 | Pattern Specification (ISO 5458:2018) | 262 |
| 10.7 | The Tolerance of a Profile in the ASME Standards | 265 |
| 10.7.1 | Composite Profile Tolerancing | 265 |
| 10.7.2 | Unilateral and Unequally Disposed Profile Tolerance | 265 |
| 10.7.3 | Coplanarity | 267 |
| 10.7.4 | The New Symbols (ASME Y14.5:2018) | 267 |
| 11 | Run-Out Tolerances | 271 |
| 11.1 | Introduction | 271 |
| 11.2 | Circular Run-Out | 273 |
| 11.3 | Total Run-Out | 275 |
| 11.4 | Run-Out Control in the ASME Y14.5 Standards | 277 |
| 11.4.1 | Run-Out on a Tangent Plane | 279 |
| 11.4.2 | Run-Out Tolerance Application to an Assembly | 280 |

| | |
|---|-----|
| 12 Geometrical Specification for Non-Rigid Parts | 283 |
| 12.1 Non-Rigid Parts | 283 |
| 12.2 The ISO 10579-NR Standard | 284 |
| 12.3 Non-Rigid Parts in the ASME Y14.5:2018 Standard | 285 |
| Reference | 290 |
| 13 Linear Sizes | 291 |
| 13.1 Introduction | 291 |
| 13.2 The ISO 14405 Standards: Terms and Definitions | 292 |
| 13.3 Default Specification Operator for Size | 294 |
| 13.4 Drawing Indications | 295 |
| Reference | 299 |
| Bibliography | 301 |
| Index | 303 |